

CN80 drives 50~83mm (2"~3 1/4") coil nails

MAX



COIL NAILER

WARNING
 TO PREVENT SERIOUS ALERT FROM
 FINGER AND TOE INJURY
 • READ OPERATION MANUAL
 • OPERATION AND OTHER WORK AREA
 SHOULD ALWAYS WEAR SAFETY GOGGLES
 • DISCONNECT AIR WHEN CLEANING A JAW
 • DO NOT USE TOOL, NOT IN USE
 • DO NOT EXCEED 90 PSI
 • KEEP FINGER OFF TRIGGER WHEN NOT DRIVING
 FASTENERS
 CN8000

• COLLATION
 WIRE



For full-sequential trip operation,
 D.S. VALVE (Optional) is provided.

FEATURES

- Newly designed head valve brings you speedy nailing performance.
- Rugged magazine.
- Can drive 300 nails speedily and continuously by full-loading.
- Flat angle magazine allows toenailing.
- Multi-directional exhaust deflector.
- Equipped with Dust cover and body protector.

TOOL SPECIFICATIONS

MODEL	CN80
WEIGHT	3.7kg (8.2lbs)
DIMENSIONS	362(H) × 132(W) × 307(L)mm 14 1/4" × 4 3/16" × 12 1/8"
LOAD CAPACITY	300-Nails
OPERATING PRESSURE	5~7kg/cm ² (Regulator) 70~100psi

The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve quality of our products.

APPLICATIONS

- Making export wooden boxes. • Crating.
- Making wooden fence. • Heavy-duty packaging.
- General construction including siding, decking, panel sheathing.

FASTENERS AVAILABLE

SMOOTH SHANK



SCREW SHANK



RING SHANK



SHANK DIA.	2.5~3.3mm .099"~.131"
LENGTH	50~83mm 2"~3 1/4"



MAX CO., LTD.

6-6, NIHONBASHI, HAKOZAKI-CHO, CHUO-KU, TOKYO, JAPAN
 PHONE: TOKYO 3669-8131 FAX: TOKYO 3669-7104

Distributor: