

Product information

Rotary Hammer SDS+ 26mm



Satisfying the professional's needs

HR2630

Impact energy	2.4 J
Max in concrete (TCT bit)	26 mm
Max in concrete (TCT core)	68 mm
Max in concrete (Diamond core)	80 mm
Max in wood	32 mm
Max in steel	13 mm
Impacts per minute	0 - 4,600 ipm
Input Wattage	800 w
Net weight	2.8 kg
No Load Speed	0 - 1200 rpm
Vibration: Chiselling	9.5 m/sec ²
Vibration: Hammer Drilling	15.5 m/sec ²
Noise sound pressure	91 dB(A)
Noise K factor	3 dB(A)
Noise sound power	102 dB(A)
Vibration: Drilling into metal	2.5 m/sec ²



STANDARD EQUIPMENT: Side handle, Depth stop, Carry case

- Modified operation-mode change lever enables switch from 'Rotation' to 'Hammering' mode and vice-versa without rotating the chuck.
- 3 mode operation: Rotation only / Rotation with hammering / Hammering only
- One touch sliding chuck for easy bit installation and removal.
- Variable speed control by trigger
- Forward/reverse rotation
- Torque limiter
- Double Insulation
- 40 different bit angle settings
- Compact and lightweight design
- Depth stop
- Ergonomically designed handle with rubberised soft grip fits your hand perfectly to provide maximum control and comfort.

Details correct as of: 23-5-2017

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makita.com