

SENCO®

**THINK FAST,
THINK DURASPIN.**



DURASPIN®
TECHNOLOGY



DURASPIN® Technology continues to evolve...
to get the job done faster and more efficiently

SENCO SCREW SYSTEM

SENCO'S NEW DURASPIN COLLATED SCREW SYSTEM RANGE

Senco's iconic DuraSpin screw fastening system has evolved to a new level of speed, power and efficiency. Senco introduces the next generation of its collated auto-feed screwdrivers in traditional corded versions as well as new compact 18-volt 3Ah Li-ion battery powered units that can drive between 1200 to 1400 screws per charge, depending on the screw length and application material.

UP TO
25%
MORE POWER



UP TO
30%
MORE SPEED

THE WORLDS LEADING COLLATED SCREW SYSTEM:

- ✓ HIGHER TORQUE
- ✓ HIGHER SPEED
- ✓ HIGHER PRODUCTIVITY

NEW BATTERY

The new battery is according to the latest standards of Li-ion battery technology. The battery incorporates a charge indicator, is more compact and lighter than previous models and has a much longer lifetime.

UP TO
100%
MORE SCREWS
PER BATTERY CHARGE



SENCO®

ICONS



Wood construction



Packaging



Drywall



Roofing /sheathing



General Joinery



The tool will be delivered in a case

CONTENTS

FEATURES & BENEFITS 4

COLLATED SCREW SYSTEMS 6

ACCESSORIES 9

COLLATED SCREWS 10

THE HISTORY OF SENCO DURASPIN

Senco is a leading and highly respected manufacturer of pneumatic collated nailing and stapling systems. In 2000 Senco introduced the first DuraSpin collated screw driver. DuraSpin quickly became the preferred choice for professional dry-liners, carpenters and general builders who saw the opportunity to easily improve their productivity.

By the mid 2000's DuraSpin had become one of the greatest successes in Senco's history, with many industry awards recognising its performance capabilities and supporting its success in becoming a regular performer on most construction sites.

In respect to the successes of the original DuraSpin tool range, Senco recognised that to take the product to the next level it required a completely new design that would benefit from the extensive knowledge Senco gained in the collated screw market. In conjunction with the latest available technologies Senco has produced a tool boasting performance features and benefits that cannot be compared to the original product line. DuraSpin technology has now evolved to get your work done even faster and more efficiently:

Think Fast, Think Senco DuraSpin



COPYRIGHT

Verpa Senco B.V.
Pascalleen 88
8218 NJ Lelystad,
The Netherlands
info@senco-emea.com
© Verpa-Senco 2013

All rights reserved; No rights may be derived from the information in this publication.

FEATURES & BENEFITS

TOOL FREE ADJUSTABLE NOSE PIECE

With easy-to-read length markings, adjusts to screw lengths of 75mm

QUICK SLIDE BIT RELEASE

Move the slide and the bit easily drops in or out



CORNER FIT ACCESS

- Patent-Pending Feed System
Fully collapsible feed system provides access to tight spaces
- Belt-drive mechanism:
Delivers smooth operation and requires less user force per drive
- Improved line of sight



SUPER HARD DRIVE BITS

The longest-lasting drive bits available



ADJUSTABLE DEPTH-OF-DRIVE WITH LOCK

- For flush drives or countersinks
- Push lock eliminates depth creep and delivers consistent drives
- Easy view depth setting window

EASY LOAD SYSTEM

Improved rail design for faster and easy loading

LANDING STRIP





SENCO®

REVERSE SWITCH

To back out driven screws

PATENTED CLUTCH DESIGN

Delivers quiet and smooth operation



1 YEAR
LIMITED
WARRANTY



HIGH TORQUE MOTOR

Specifically designed speeds and torques to drive screws with no motor drag

SECOND HAND GRIP

Helps combat worker fatigue

COMFORTABLE GRIP

Ergonomically designed for extra comfort and better productivity with less exertion

TRIGGER LOCK

For continuous use applications

BELT HOOK

Adjustable and reversible to keep the tool within reach for improved productivity

VARIABLE SPEED TRIGGER

Allows user to regulate RPMs for self-tapping screws into steel and other applications

INCLUDES

TWO NOSE PIECES:

- 1. Wood Applications:**
Ensures a straight drive in harder materials
- 2. Drywall Applications:**
Dimples drywall just right

BLOW MOLDED CASE



2 EXTRA BITS

DC TOOLS:
2 x 18V 3Ah Li-Ion Batteries with Charger

AC TOOLS:
3,5m Rubber Power Cord

COLLATED SCREW SYSTEMS

HEAVY DUTY SCREW SYSTEM DS5525-18V



TECHNICAL INFORMATION

LxWxH	381x86x241 mm
Weight	2,6 kg
RPM	2500
Torque	8Nm
Magazine capacity	50
Max. screw length	55mm
Battery	18V 3Ah Li-ion
Screw per charge	up to 1400
Recharge time	1 hour

APPLICATIONS


Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION

DESCRIPTION	ART. NR
DS5525-18V EU	7X2001N
DS5525-18V UK	7X7001N



* 13-50 mm screws require special nosepiece

HEAVY DUTY SCREW SYSTEM DS5525-AC



TECHNICAL INFORMATION

LxWxH	425x70x233 mm
Weight	2,1 kg
RPM	2500
Torque	11Nm
Magazine capacity	50
Max. screw length	55mm

APPLICATIONS


Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION

DESCRIPTION	ART. NR
DS5525-AC EU	7U2001N
DS5525-AC UK	7U7001N



* 13-50 mm screws require special nosepiece

HIGH SPEED SCREW SYSTEM DS5550-18V



TECHNICAL INFORMATION

LxWxH	381x86x241 mm
Weight	2,6 kg
RPM	5000
Torque	5Nm
Magazine capacity	50
Max. screw length	55mm
Battery	18V 3Ah Li-ion
Screw per charge	up to 1400
Recharge time	1 hour

APPLICATIONS


Drywall to wood or steel studs, subfloor, sheathing, cement board, underlayment

FEATURES

- 5000 RPM high speed motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION

DESCRIPTION	ART. NR
DS5550-18V EU	7W2001N
DS5550-18V UK	7W7001N



* 13-50 mm screws require special nosepiece



SENCO®

HIGH SPEED SCREW SYSTEM DS5550-AC

MULTI PURPOSE SCREW SYSTEM DS7525-18V

MULTI PURPOSE SCREW SYSTEM DS7525-AC



TECHNICAL INFORMATION

LxWxH	425x70x233 mm
Weight	2,1 kg
RPM	5000
Torque	7Nm
Magazine capacity	50
Max. screw length	55mm

APPLICATIONS

Drywall to wood or steel studs, subfloor, sheathing, cement board, underlayment

FEATURES

- 5000 RPM high speed motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

DESCRIPTION

DESCRIPTION	ART.NR
DS5550-AC EU	7T2001N
DS5550-AC UK	7T7001N



* 13-50 mm screws require special nosepiece



TECHNICAL INFORMATION

LxWxH	394x86x241 mm
Weight	2,7 kg
RPM	2500
Torque	8Nm
Magazine capacity	50
Max. screw length	55mm
Battery	18V 3Ah Li-ion
Screw per charge	up to 1400
Recharge time	1 hour

APPLICATIONS


Drywall to wood or steel studs, subfloor, cement board, underlayment, sheathing to steel, metal framing

FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Patented sliding screw guide
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock

DESCRIPTION

DESCRIPTION	ART.NR
DS7525-18V EU	7Y2001N
DS7525-18V UK	7Y7001N



TECHNICAL INFORMATION

LxWxH	438x70x233 mm
Weight	2,2 kg
RPM	2500
Torque	11Nm
Magazine capacity	50
Max. screw length	75mm

APPLICATIONS

Drywall to wood or steel studs, subfloor, cement board, underlayment, sheathing to steel, metal framing

FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Patented sliding screw guide
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock

DESCRIPTION

DESCRIPTION	ART.NR
DS7525-AC EU	7V2001N
DS7525-AC UK	7V7001N



THINK FAST, THINK SENCO DURASPIN.

ACCESSORIES



EASY DRIVER SCREW SYSTEM DS300-AC



TECHNICAL INFORMATION

LxWxH	800-1054x109x175 mm
Weight	3,9 kg
RPM	3300
Torque	6Nm
Magazine capacity	50
Max. screw length	75mm

APPLICATIONS

Decking, subfloors

FEATURES

- Depth adjustment allows precise countersinking of screws
- Trigger lock
- Height adjustable handle
- Patented clutch design for long-lasting durability

DESCRIPTION

DESCRIPTION	ART. NR
DS300-AC EU 230V	1P2001N
DS300-AC UK 230V	1P7001N
DS300-AC UK 110V	1P7002N



ROOFING SCREW SYSTEM DS300-AC



TECHNICAL INFORMATION

LxWxH	800-1054x109x175 mm
Weight	3,9 kg
RPM	3300
Torque	6Nm
Magazine capacity	50
Max. screw length	75mm

APPLICATIONS


Specially designed for roofing application

FEATURES

- Specifically designed for roofing
- Adjustable depth of drive
- Height adjustable handle
- Trigger lock
- Patented clutch design for long-lasting durability

DESCRIPTION

DESCRIPTION	ART. NR
DS300-AC roofing 230V	1P2001NX
DS300-AC roofing UK 230V	1P7001NX





SENCO®

DRIVE BITS IN BLISTERPACK

DESCRIPTION

ART.NR

BITS FOR DS5525, DS5550

Screw bit PH2	EA0326B
Screw bit SQ2	EA0327B
Screw bit PZ2	EA0335B*
Screw bit TX20	EA0336B*
Screw bit Senco drive	EA0333B*

BITS FOR DS7525

Screw bit PH2	EA0329B
Screw bit SQ2	EA0330B
Screw bit PZ2	EA0337B*
Screw bit TX20	EA0338B*
Screw bit Senco drive	EA0334B*

BITS FOR DS300AC

Screw bit PH2	EA0128B
Screw bit SQ2	EA0127B

* article could have longer delivery time

Select the bit that's right for the job



CHARGER



DESCRIPTON

ART.NR.

Battery charger 18V EU	VB0157
Battery charger 18V UK	VB0159

NOSE PIECES



DESCRIPTON

ART.NR.

Nose piece for drywall	
DS5525/DS5550	FC0886EU
DS7525	FC0906EU

DESCRIPTON

ART.NR.

Nose piece for wood	
DS5525/DS5550	FB0162EU
DS7525	FB0160EU

BATTERY



DESCRIPTON

ART.NR.

Battery 18V 3,0Ah	VB0162
-------------------	--------




THINK FAST, THINK Senco DURASPIN.


COLLATED SCREWS

INDEX


Screw head



Screw point



Recess



Screw thread




Material/Finish

- Phosphate
- Clear zinc
- Yellow zinc
- Green ruspert II
- Stainless Steel
- Weatherex II

Items marked * could have a longer lead time.



DRYWALL TO WOOD




Size	Material/Finish	Head Ø	Art.Nr
3,9 x 25mm	Phosphate	8,00-8,50	39A25MP
3,9 x 30mm	Phosphate	8,00-8,50	39A30MP
3,9 x 35mm	Phosphate	8,00-8,50	39A35MP
3,9 x 41mm	Phosphate	8,00-8,50	39A41MP *
3,9 x 45mm	Phosphate	8,00-8,50	39A45MP
3,9 x 50mm	Phosphate	8,00-8,50	39A50MP
3,9 x 55mm	Phosphate	8,00-8,50	39A55MP
4,5 x 75mm	Phosphate	8,00-8,50	45A75MP
3,9 x 32mm	Clear Zinc	8,00-8,50	39A32MC-5
3,9 x 35mm	Clear Zinc	8,00-8,50	39A35MC-5 *
3,9 x 42mm	Clear Zinc	8,00-8,50	39A42MC-5
3,9 x 55mm	Clear Zinc	8,00-8,50	39A55MC-5 *



SENCO®

DRYWALL TO WOOD




Size	Material/Finish	Head Ø	Art.Nr
○ 3,9 x 30mm	Clear Zinc	8,00-8,50	39N30MC-5
○ 3,9 x 42mm	Clear Zinc	8,00-8,50	39N42MC-5 *
○ 3,9 x 55mm	Clear Zinc	8,00-8,50	39N55MC-5 *

DRYWALL TO WOOD OR LIGHT STEEL (UP TO 1MM)




Size	Material/Finish	Head Ø	Art.Nr
○ 3,9 x 30mm	Clear Zinc	6,00-6,50	39T30MC-5 *
○ 3,9 x 40mm	Clear Zinc	6,00-6,50	39T40MC-5 *
○ 3,9 x 50mm	Clear Zinc	6,00-6,50	39T50MC-5 *

DRYWALL TO LIGHT STEEL (UP TO 1MM)



Size	Material/Finish	Head Ø	Art.Nr
○ 3,5 x 25mm	Clear Zinc	8,00-8,50	35P25MC-5 *
○ 3,5 x 40mm	Clear Zinc	8,00-8,50	35P40MC-5

DRYWALL TO LIGHT STEEL (UP TO 1MM)



Size	Material/Finish	Head Ø	Art.Nr
○ 3,5 x 35mm	Phosphate	8,00-8,50	35B35MP
○ 3,5 x 45mm	Phosphate	8,00-8,50	35B45MP
○ 3,9 x 25mm	Phosphate	8,00-8,50	39B25MP
○ 3,9 x 35mm	Phosphate	8,00-8,50	39B35MP
○ 3,9 x 45mm	Phosphate	8,00-8,50	39B45MP
○ 3,9 x 55mm	Phosphate	8,00-8,50	39B55MP *

DRYWALL TO HEAVY STEEL (UP TO 3MM)




Size	Material/Finish	Head Ø	Art.Nr
○ 3,5 x 25mm	Phosphate	8,00-8,47	35Q25MP *
○ 3,5 x 35mm	Phosphate	8,00-8,48	35Q35MP *
○ 3,5 x 40mm	Phosphate	8,00-8,49	35Q40MP *
○ 3,5 x 45mm	Phosphate	8,00-8,50	35Q45MP *
○ 3,5 x 25mm	Clear Zinc	8,00-8,50	35Q25MC-5
○ 3,5 x 35mm	Clear Zinc	8,00-8,50	35Q35MC-5
○ 3,5 x 40mm	Clear Zinc	8,00-8,50	35Q40MC-5 *
○ 3,5 x 45mm	Clear Zinc	8,00-8,50	35Q45MC-5

THINK FAST, THINK SENCO DURASPIN.

COLLATED SCREWS

DRYWALL TO WOOD OR LIGHT STEEL (UP TO 1MM)




Size	Material/Finish	Head Ø	Art.Nr	
3,9 x 25mm	Phosphate	8,00-8,45	39S25MP	*
3,9 x 35mm	Phosphate	8,00-8,50	39S35MP	*
3,9 x 40mm	Phosphate	8,00-8,47	39S40MP	*
3,9 x 45mm	Phosphate	8,00-8,48	39S45MP	*
3,9 x 55mm	Phosphate	8,00-8,48	39S55MP	*
3,9 x 25mm	Clear Zinc	8,00-8,50	39S25MC-5	*
3,9 x 30mm	Clear Zinc	8,00-8,50	39S30MC-5	*
3,9 x 32mm	Clear Zinc	8,00-8,50	39S32MC-5	
3,9 x 35mm	Clear Zinc	8,00-8,50	39S35MC-5	
3,9 x 40mm	Clear Zinc	8,00-8,50	39S40MC-5	*
3,9 x 42mm	Clear Zinc	8,00-8,50	39S42MC-5	
3,9 x 50mm	Clear Zinc	8,00-8,50	39S50MC-5	*

GYPSUM FIBER BOARD TO LIGHT STEEL (UP TO 1MM)




Size	Material/Finish	Head Ø	Art.Nr
3,9 x 30mm	Phosphate	6,70-7,00	39J30MP
3,9 x 45mm	Phosphate	6,70-7,00	39J45MP

GYPSUM FIBER BOARD TO WOOD OR LIGHT STEEL (UP TO 1MM)



Size	Material/Finish	Head Ø	Art.Nr	
3,9 x 30mm	Clear Zinc	6,00-6,50	39U30MC-5	*
3,9 x 40mm	Clear Zinc	6,00-6,50	39U40MC-5	*
3,9 x 50mm	Clear Zinc	6,00-6,50	39U50MC-5	*

HARD FIBER TO WOOD OR LIGHT STEEL (UP TO 1MM)



Size	Material/Finish	Head Ø	Art.Nr	
3,9 x 30mm	Clear Zinc	6,70-7,00	39JS30MC	*
3,9 x 45mm	Clear Zinc	6,70-7,00	39JS45MC	*

HARD FIBER BOARD TO LIGHT STEEL (UP TO 1MM)





Size	Material/Finish	Head Ø	Art.Nr	
4,2 x 35mm	Phosphate	7,40-7,80	42UM35MP	*
4,2 x 38mm	Phosphate	7,40-7,80	42UM38MP	




SENCO®

GENERAL WOOD TO WOOD








Size	Material/Finish	Head Ø	Art.Nr	
○ 4,0 x 25mm	Clear Zinc	8,00-8,50	40K25MC	*
○ 4,0 x 30mm	Clear Zinc	8,00-8,50	40K30MC	*
○ 4,0 x 35mm	Clear Zinc	8,00-8,50	40K35MC	*
○ 4,0 x 40mm	Clear Zinc	8,00-8,50	40K40MC	*
○ 4,0 x 45mm	Clear Zinc	8,00-8,50	40K45MC	*
○ 4,0 x 50mm	Clear Zinc	8,00-8,50	40K50MC	*
○ 4,0 x 55mm	Clear Zinc	8,00-8,50	40K55MC	*
○ 4,0 x 60mm	Clear Zinc	8,00-8,50	40K60MC	*
● 4,2 x 25mm	Yellow Zinc	8,00-8,50	42K25MY	
● 4,2 x 30mm	Yellow Zinc	8,00-8,50	42K30MY	
● 4,2 x 35mm	Yellow Zinc	8,00-8,50	42K35MY	
● 4,2 x 45mm	Yellow Zinc	8,00-8,50	42K45MY	

FLOORING WOOD TO WOOD (CHIPBOARD)








Size	Material/Finish	Head Ø	Art.Nr	
○ 4,0 x 25mm	Clear Zinc	8,00-8,50	40H25MC	*
○ 4,0 x 30mm	Clear Zinc	8,00-8,50	40H30MC	*
○ 4,0 x 35mm	Clear Zinc	8,00-8,50	40H35MC	
○ 4,0 x 40mm	Clear Zinc	8,00-8,50	40H40MC	
○ 4,0 x 45mm	Clear Zinc	8,00-8,50	40H45MC	*
○ 4,0 x 50mm	Clear Zinc	8,00-8,50	40H50MC	*
○ 4,0 x 55mm	Clear Zinc	8,00-8,50	40H55MC	*
○ 4,0 x 60mm	Clear Zinc	8,00-8,50	40H60MC	*
● 4,2 x 25mm	Yellow Zinc	8,00-8,50	42H25MY	*
● 4,2 x 30mm	Yellow Zinc	8,00-8,50	42H30MY	*
● 4,2 x 35mm	Yellow Zinc	8,00-8,50	42H35MY	*
● 4,2 x 45mm	Yellow Zinc	8,00-8,50	42H45MY	*

WOOD TO WOOD (CHIPBOARD)



Size	Material/Finish	Head Ø	Art.Nr	
● 4,2 x 35mm	Yellow Zinc	8,00-8,50	42KS35MY	*
● 4,2 x 40mm	Yellow Zinc	8,00-8,50	42KS40MY	*
● 4,2 x 45mm	Yellow Zinc	8,00-8,50	42KS45MY	*
● 4,2 x 50mm	Yellow Zinc	8,00-8,50	42KS50MY	*

FLOORING WOOD TO WOOD





Size	Material/Finish	Head Ø	Art.Nr
● 4,5 x 75mm	Yellow Zinc	8,00-8,50	45F75MY

THINK FAST, THINK Senco DURASPINE.


COLLATED SCREWS

FLOORING WOOD TO WOOD





Size	Material/Finish	Head Ø	Art.Nr
4,5 x 60mm	Yellow Zinc	8,00-8,50	45X60MY
4,5 x 65mm	Yellow Zinc	8,00-8,50	45X65MY *
4,5 x 70mm	Yellow Zinc	8,00-8,50	45X70MY *

FLOORING WOOD TO WOOD



Size	Material/Finish	Head Ø	Art.Nr
4,2 x 35mm	Yellow Zinc	7,00-7,50	42Z35MY *
4,2 x 45mm	Yellow Zinc	7,00-7,50	42Z45MY *
4,2 x 55mm	Yellow Zinc	7,00-7,50	42Z55MY

FLOORING WOOD TO WOOD (MEDIUM)



Size	Material/Finish	Head Ø	Art.Nr
4,2 x 25mm	Yellow Zinc	7,00-7,50	42R25MY *
4,2 x 35mm	Yellow Zinc	7,00-7,50	42R35MY *
4,2 x 40mm	Yellow Zinc	7,00-7,50	42R40MY *
4,2 x 45mm	Yellow Zinc	7,00-7,50	42R45MY
4,2 x 50mm	Yellow Zinc	7,00-7,50	42R50MY
4,2 x 55mm	Yellow Zinc	7,00-7,50	42R55MY *
4,5 x 75mm	Yellow Zinc	7,00-7,50	45R75MY *
4,2 x 40mm	Ruspurt II	7,00-7,50	42R40MR *
4,2 x 50mm	Ruspurt II	7,00-7,50	42R50MR *
4,2 x 55mm	Ruspurt II	7,00-7,50	42R55MR *
4,5 x 50mm	Ruspurt II	7,00-7,50	45R50MR *
4,5 x 55mm	Ruspurt II	7,00-7,50	45R55MR *
4,2 x 50mm	Stainless Steel	7,00-7,50	42R50MS *
4,2 x 55mm	Stainless Steel	7,00-7,50	42R55MS *
4,2 x 45mm	Weatherex II	7,00-7,50	42R45MW *
4,5 x 65mm	Weatherex II	7,00-7,50	45R65MW *

FLOORING WOOD TO WOOD





Size	Material/Finish	Head Ø	Art.Nr
4,2 x 35mm	Yellow Zinc	7,00-7,50	42RH35MY *
4,2 x 40mm	Yellow Zinc	7,00-7,50	42RH40MY *
4,2 x 45mm	Yellow Zinc	7,00-7,50	42RH45MY
4,2 x 50mm	Yellow Zinc	7,00-7,50	42RH50MY *
4,2 x 55mm	Yellow Zinc	7,00-7,50	42RH55MY *
4,5 x 65mm	Yellow Zinc	7,00-7,50	45RH65MY *
4,5 x 75mm	Yellow Zinc	7,00-7,50	45RH75MY *
4,2 x 40mm	Ruspurt II	7,00-7,50	42RH40MR *
4,2 x 50mm	Ruspurt II	7,00-7,50	42RH50MR *
4,2 x 55mm	Ruspurt II	7,00-7,50	42RH55MR *
4,5 x 65mm	Ruspurt II	7,00-7,50	45RH65MR *
4,5 x 75mm	Ruspurt II	7,00-7,50	45RH75MR *
4,2 x 35mm	Stainless Steel	7,00-7,50	42RH35MS *
4,2 x 40mm	Stainless Steel	7,00-7,50	42RH40MS *
4,2 x 45mm	Stainless Steel	7,00-7,50	42RH45MS *
4,2 x 50mm	Stainless Steel	7,00-7,50	42RH50MS *
4,2 x 55mm	Stainless Steel	7,00-7,50	42RH55MS
4,5 x 75mm	Stainless Steel	7,00-7,50	45RH75MS *





SENCO®

DECKING WOOD TO WOOD





Size	Material/Finish	Head Ø	Art.Nr	
4,5 x 50mm	Stainless Steel	8,00-8,50	45D50MSA	*
4,5 x 65mm	Stainless Steel	8,00-8,50	45D65MSA	
4,5 x 75mm	Stainless Steel	8,00-8,50	45D75MSA	*

FLOORING/DECKING WOOD TO WOOD (SOFT)





Size	Material/Finish	Head Ø	Art.Nr	
4,2 x 35mm	Yellow Zinc	8,00-8,50	42Y35MY	*
4,2 x 40mm	Yellow Zinc	8,00-8,50	42Y40MY	*
4,2 x 50mm	Yellow Zinc	8,00-8,50	42Y50MY	*
4,2 x 55mm	Yellow Zinc	8,00-8,50	42Y55MY	

FLOORING/DECKING WOOD TO WOOD (SOFT)





Size	Material/Finish	Head Ø	Art.Nr
4,2 x 50mm	Weatherex II	8,00-8,50	42W50MW
4,2 x 55mm	Weatherex II	8,00-8,50	42W55MW
4,5 x 65mm	Weatherex II	8,00-8,50	45W65MW
4,5 x 75mm	Weatherex II	8,00-8,50	45W75MW
4,2 x 50mm	Yellow Zinc	8,00-8,50	42W50MY
4,2 x 55mm	Yellow Zinc	8,00-8,50	42W55MY
4,5 x 65mm	Yellow Zinc	8,00-8,50	45W65MY
4,5 x 75mm	Yellow Zinc	8,00-8,50	45W75MY

STEEL TO STEEL (UP TO 3 OR 4,4MM)



Size	Material/Finish	Head Ø	Art.Nr	
4,2 x 13mm	Clear Zinc	7,77-8,18	42OP13MC	
4,2 x 16mm	Clear Zinc	7,77-8,18	42OP16MC	
4,2 x 19mm	Clear Zinc	7,77-8,18	42OP19MC	*

WOOD TO HEAVY STEEL (UP TO 3MM)



Size	Material/Finish	Head Ø	Art.Nr	
4,2 x 35mm	Clear Zinc	8,00-8,50	42GS35MC	*
4,2 x 41mm	Clear Zinc	8,00-8,50	42GS41MC	
4,2 x 65mm	Clear Zinc	8,00-8,50	42GS65MC	*

THINK FAST, THINK SENCO DURASPIN.

