

SENCO®Performance. Power.
Productivity.™**SN901XP**


XtremePro™ 3¼" Clipped Head Framing Nailer

This well-balanced light weight XP framing nailer packs plenty of power and won't leave you fatigued at the end of the day. Drives ring, screw, and smooth-shank clipped head nails. SENCORP XP tools are specifically engineered for demanding pros and demanding environments. Built with enhanced features and superior components – SENCORP's XP tools always provide the best performance and longest life backed by a 5-year limited warranty.



Specifications

Item#	4Z0001N
Selectable actuation trigger	
Reg. Operating Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 cycles per min.)	5.2 scfm
Air Inlet	3/8" NPT
Tool Weight	7.8 lbs (3.54 kg)
Height	11.9" (302 mm)
Length	17.3" (440 mm)
Width	4.5" (114 mm)
Fastener Capacity	83



Fastener Specifications

Shank Diameter	.113" - .135"
Fastener Range	2" - 3¼"
Finish	Bright Basic, Galv. & Stainless
Collation	34° angled strip

Applications

Framing, sheathing, truss building, sub-flooring and decks. Other applications include crate and box assembly, pallet making, furniture frame assembly and fencing.

Features and Benefits

- Well balanced, ergonomic design
- Uses less air to drive nails- Highly efficient internal design
- Dry Fire Lockout
- Reduced jams and mis-feeds - Patented TrueDrive magazine
- Low profile design fits easily between studs and joists
- Retractable Rafter Hanger
- Contact or sequential trigger actuation - Patented drive selector
- 5-year limited warranty


*Choose the right actuation mode!

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how SENCORP will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596, or visit our web site at: www.senco.com.

Features



Smooth-Shank

Length	Item Code	Carton Count	Finish
2 x .113	GC21APBK	2.5M	Bright
2 1/4 x .113	GC23APBX	2.5M	Bright
2 3/8 x .113	GC24APBX	2.5M	Bright
2 1/2 x .113	GC25APBX	2.5M	Bright
3 x .120	HC27APBX	2.5M	Bright
3 x .131	KC27APBX	2.5M	Bright
3 1/4 x .131	KC28APBX	2.5M	Bright
3 1/4 x .120	HC28APBX	2.5M	Bright
3 1/4 x .131	KC28APBX	2.5M	Bright
2 1/2 x .113	GC25AABX	2.5M	Galv
3 x .120	HC27AABX	2.5M	Galv
3 x .131	KC27AABX	2.5M	Galv
2 3/8 x .113	GC24ASBX	2.5M	Hot Dip
3 x .120	HC27ASBX	2.5M	Hot Dip
3 x .131	KC27ASBX	2.5M	Hot Dip
3 1/4 x .131	KC28ASBX	2.5M	Hot Dip
3 x .131	KC27AGBK	1.M	Stainless
3 1/4 x .131	KC28AGB	1.M	Stainless

Screw-Shank-Strip

Length	Item Code	Carton Count	Finish
3 x .120	HF27EPAK	3.1M	Bright
3 x .120	HF27EDB	1.M	Exterior
3 x .120	HF27AGBK	1.M	Stainless

Ring-Shank

Length	Item Code	Carton Count	Finish
2 x .113	GE21APAK	2.5M	Bright
2 3/8 x .113	GE24APBX	2.5M	Bright
2 x .113	GE21AAAK	2.M	Galv
2 3/8 x .113	GE24AABX	2.5M	Galv
3 x .120	HE27AABX	2.5M	Galv
2 x .113	GE21ASBK	2.5M	Hot Dip
2 3/8 x .113	GE24ASBX	2.5M	Hot Dip
3 x .120	HE27ASBX	2.5M	Hot Dip
2 3/8 x .113	GE24AGBK	1.M	Stainless
3 x .120	HE27AGBK	1.M	Stainless

SENCO® RoundStrip™ 34° Smooth Round Head Nails

Length	Item Code	Carton Count	Finish
2 3/8 x .113	G524APBX	2.5M	Bright
3 x .120	H527APBX	2.5M	Bright
3 x .131	K527APBX	2.5M	Bright
3 1/4 x .131	K528APBX	2.5M	Bright
3 1/2 x .131	K529APBX	2.5M	Bright
2 x .113	G521ASBK	2.M	Hot Dip
2 3/8 x .113	G524ASBX	2.5M	Hot Dip
3 x .120	H527ASBX	2.5M	Hot Dip
3 x .131	K527ASBX	2.5M	Hot Dip
3 1/4 x .131	K528ASBX	2.5M	Hot Dip

SENCO® RoundStrip™ 34° Ring Round Head Nails

Length	Item Code	Carton Count	Finish
2 3/8 x .113	G624APBX	2.5M	Bright
3 x .120	H627APBX	2.5M	Bright
2 x .113	G621ASBK	2.M	Hot Dip
2 3/8 x .113	G624ASBX	2.5M	Hot Dip
3 x .120	H627ASBX	2.5M	Hot Dip
3 x .131	K627ASBX	2.5M	Hot Dip