

# GREX.





### P650L - 23 Ga. 2" Length Headless Pinner with Auto Lock-out

Introducing the P650L with Auto Lock-Out and 2" fastener capability. Adding the "L" (Auto Lock-Out) to the GREX P650L means: Less rework, less down time, and less tool and project damage. Now drive longer fasteners and prevent dry-firing with the same great quality and features expected from GREX.

We added the Auto Lock-Out for those difficult, more critical jobs such as overhead crown molding. Dry-firing can cause damage to the tool and might cause damage to an expensive project. To prevent dry-firing, the Auto Lock-Out locks the GREX P650L with approximately 6-8 pins remaining in the magazine. The Auto Lock-Out over-ride button overrides the lockout allowing use of the remaining pins to tack a project-piece in place freeing the operator to reload.

The high tolerance precision machined hardened steel driver, Posit-Lock™ nose cover and nose guide assembly aligns and seats the headless pin for optimal drive performance. What is Posit-Lock  $^{\text{TM}}$  - it's tight tolerance, durability and functionality that reduces jams to a minimum.

The P6 Series comes in seven different designs: P630, P635, P645, P645L, P650, P650L and the P650LX.

GREX, demanded by Pros, for more than 20 years has helped professionals rise to the top of their trade. Now explore.

- Seven different designs: P630, P635, P645, P645L, P650, P650L, P650LX
- Auto Lock-Out prevents dry-firing and project damage
- Auto Lock-Out over-ride button allows use of the remaining pins
- Drives 23-gauge headless pins ranging from  $1/2^{\prime\prime}$  to  $2^{\prime\prime}$  in length
- Patented magazine self-adjusts for 13 different fastener lengths
- Narrow nose design for access to more tight areas and angles - Powerful motor to drive fasteners into hardwood
- Lightweight aluminum body designed for mobility and all day continuous use
- Precision machined and aluminum cylinder and piston valve
- Drop-in fastener loading for quick and easy re-loading
- Fastener indicator window shows pin supply; alerting operator to reload
- Double trigger safety lock prevents accidental firing
- Posit-Lock™ nose cover for tight tolerance and access to the pin chamber
- Swivel air coupler helps keep air hose tangle-free
- Rear exhaust with silencer reduces noise and directs exhaust air away
- Belt hook keeps your GREX tool at your side; left or right mounted
- No-mar rubber tip prevents marring of work surface
- No-mar guidelines for accurate pinning
- Rear magazine cap with hex wrench and spare no-mar tip storage
- Rubber handgrip for a firm comfortable grip

## Specifications:

Dimensions: 8.75"H x 7.75"L x 1.5"W (22.2 x 19.7 x 3.8 cm)

Weight: 2.68 lbs. (1.2 kgs.)

Operating Pressure: 60 ~ 110 psi (4 ~ 7.6 bars)

Fastener Type:23 Gauge Headless Pins

Fastener Range: 1/2" ~ 2" (12mm ~ 50mm) excluding 1 1/4" (32mm)

Fastener Capacity: 1 strip (approx. 100 pins) Air Inlet: 1/4" (6mm) NPT male plug

## **Applications:**

Overhead applications, Light wood assembly, Finish and trim work, Molding and decorative trim, Dowel and joint pinning, Mirror and picture frame assembly, Lightweight panelling, External softwood trim, Rattan furniture, Glazing strips, Craft work, Window beading, Display and sign work, Etc...

© 1996-2009 Grex Power Tools. All rights reserved.

