

**FINISH THE JOB STRONG.**

● LAST NAIL LOCK-OUT WITH OVERRIDE SYSTEM

● PIN INDICATOR AS REMINDER FOR RELOAD

**ERGONOMIC HANDLE ON GRAVITY CASTED FRAME**  
providing user comfort and durability

**DOUBLE SAFETY TRIGGER**  
ensures user safety

**EASY ACCESS BOLTS & WRENCH**  
for jam clearing and depth adjustment

**NO-MAR PAD AND NARROW NOSE**  
allows precise pin placement and clean finish on tight corners

**REAR EXHAUST**  
with built-in muffler

**REVERSIBLE BELT HOOK**  
clips nailer securely to user's tool belt

**AUTO PIN LENGTH ADJUST**  
**EASY SIDE LOADING SYSTEM**  
minimizes downtime



### TOOL SPECIFICATION

<b>Weight:</b>	2.7lbs (1.2kg)
<b>Height:</b>	8.9" (226mm)
<b>Width:</b>	1.8" (47mm)
<b>Length:</b>	<b>P650:</b> 7.9" (200mm) <b>P850:</b> 10.2" (260mm)
<b>Operating pressure:</b>	70 to 100 PSI (5-7 bars)
<b>Firing mode:</b>	Dual Trigger
<b>Applications:</b>	Cabinets, Mirrors, Picture Frames, Finish and Trim

### FASTENER SPECIFICATION

<b>Collation:</b>	Glue Strip
<b>Pin Lengths:</b>	<b>P650:</b> 1/2"-2" (13- 50mm) <b>P850:</b> 5/8"-2"(16- 50mm)
<b>Pin Diameter:</b>	<b>P650:</b> 23 Ga (0.64mm) <b>P850:</b> 21 Ga (0.84mm)
<b>Shank Type:</b>	Smooth
<b>Load Capacity:</b>	100

Nailfast

Units 4-5 Nobel Court, Nobel Road, Wester Gourdie Ind. Est., Dundee, DD2 4UH.

t: 01382 622993

e: sales@nailfast.co.uk

www.nailfast.co.uk