

# CONSTRUCTION & PACKING STAPLER

## APPLICATION

SHEATHING / SUBFLOORING / ROOF DECKING  
FURNITURE FRAMES / PALLETS / VINYL SIDING  
CRATE AND BOX ASSEMBLY



PR-16951P

- 1 ADJUSTABLE AIR DEFLECTOR**
- 2 ANTI-DOUBLE FIRE MECHANISM, SINGLE OR CONTACT FIRING:**  
No adjustment needed to switch from one to the other. (U.S. PATENT 6419140)
- 3 LOW NOISE AND LOW VIBRATION**
- 4 POWERFUL AND PATENTED DRIVER DESIGN FOR DURABLE USE**
- 5 FAST-CYCLE RATE TO 15 NAILS/SECOND (110Psi)**
- 6 ERGONOMIC DESIGN**  
Center of gravity is closer to the trigger, providing better balance, also offers the lowest recoil for a tool of its size
- 7 ADJUSTABLE WORK CONTACTING ELEMENT**  
Depth of drive adjustment element on the tool.

### 11 EASY LOADING AND PUSHER PROTECTOR DESIGN (PATENT PENDING)



### FOR FLOORING TIP



### SLIM SAFETY LEVER FOR SELECT




### 8 ONE STEP JAM CLEARANCE (PATENT PENDING)



- 9 DURABLE AND RELIABLE:**  
Rugged design will stand up to the demands of the job in any kind of weather.
- 10 LIGHTEST**  
ONLY 4.8lbs(2.18kg)

# CONSTRUCTION & PACKING STAPLER




**PRO-MEDIUM CROWN STAPLER**  
**PR-16851P**

- GAUGE SIZE  
16GA
- CROWN SIZE  
7/16" (10.6~11.2mm)
- WIDTH X THICKNESS  
.063"x.055" (1.6x1.4mm)
- WEIGHT  
4.8lbs (2.18kg)
- LOAD CAPACITY  
147 Staples
- OPERATING PRESSURE  
80~120psi (5.5-8.3kg/cm<sup>2</sup>)



**PRO-MEDIUM CROWN STAPLER**  
**PR-16951P**

- GAUGE SIZE  
16GA
- CROWN SIZE  
1/2" (12.2~12.7mm)
- WIDTH X THICKNESS  
.063"x.055" (1.6x1.4mm)
- WEIGHT  
4.8lbs (2.18kg)
- LOAD CAPACITY  
147 Staples
- OPERATING PRESSURE  
80~120psi (5.5-8.3kg/cm<sup>2</sup>)



### PR-16851K-1 SLIM SAFETY LEVER FOR SELECT

